

## Designed specifically for metal and structural plastic bonding

0568 is a purple, 0.005" thick, polyester mat epoxy film that is designed specifically for metal and structural plastic bonding. It features high shear strength of 4,500 psi, a high peel strength of 25 ppi, and exhibits excellent strength at elevated temperatures. 0568 has a long work life and multiple storage options making it very user-friendly.

<b>UNCURED</b>	
Work Life @ 25°C	120 hours
Shelf Life	6 months @ -18°C    12 months @ -40°C 5 days @ 32°C
<b>CURE OPTIONS</b>	1 hour @ 110°C (under 40 psi)
<b>CURED PROPERTIES</b>	Based on cure of 1 hour @ 110°C (under 40 psi)
Color	Purple
Specific Gravity	1.2
Lap Shear 2024T3 Clad (psi)	4,500
T-Peel Strength (ppi)	25

### KEY FEATURES

High Elevated Temperature Strength

High Peel Strength

High Shear Strength

Thickness: 0.005"

### Talk to an engineer:

[service@appli-tec.com](mailto:service@appli-tec.com)

603-685-0500 ext. 528

[www.appli-tec.com](http://www.appli-tec.com)

7 Industrial Way, Unit 1, Salem, NH 03079

The data contained herein is provided for informational purposes only and are believed to be reliable. APPLI-TEC does not guarantee suitability of this product for any resultant application or freedom from patent infringement. Furthermore, APPLI-TEC disclaims any liability for incidental and consequential damages of any kind including but not limited to lost profits.

Rev D

9/8/2017