

Page: 1 of 6

Revision: 10/06/2021 Supersedes Revision: 06/13/2017

1. Product and Company Identification

Product Code: 0720 Product Name: 0720

Company Name: Appli-Tec, Inc Phone Number: 7 Industrial Way Unit 1 (603)685-0500

7 Industrial Way Unit 1 Salem, NH 03079

Web site address: www.appli-tec.com

Emergency Contact: Contact medical emergency services

Information: Call Chemtrec for Transport Info. (800)424-9300

Intended Use: Adhesive

2. Hazards Identification

Flammable Liquids, Category 2

Skin Corrosion/Irritation, Category 3

Serious Eye Damage/Eye Irritation, Category 2

Carcinogenicity, Category 2

Toxic To Reproduction, Category 2

Specific Target Organ Toxicity (single exposure), Category 3
Specific Target Organ Toxicity (repeated exposure), Category 1







GHS Signal Word:

Danger

GHS Hazard Phrases: H225 - Highly flammable liquid and vapor.

H316 - Causes mild skin irritation.H319 - Causes serious eye irritation.H335 - May cause respiratory irritation.H351 - Suspected of causing cancer .

H361 - Suspected of damaging fertility or the unborn child .

H372 - Causes damage to organs - Lungs. through prolonged or repeated

exposure.

H3UN - 30.00 % of the mixture consists of an ingredient or ingredients of

unknown acute toxicity.

GHS Precautionary

P201 - Obtain special instructions before use.

Phrases: P202 - Do not handle until all safety precautions have been read and

understood.

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P241 - Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe vapors, mist or spray. P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P281 - Use personal protective equipment as required.

GHS Response Phrases: P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all

contaminated clothing. Rinse skin with water/shower.

Licensed to Appli-Tec GHS format



Page: 2 of 6

Revision: 10/06/2021 Supersedes Revision: 06/13/2017

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P308+313 - IF exposed or concerned: Get medical attention/advice. P312 - Call a POISON CENTER or doctor/physician if you feel unwell. P332+313 - If skin irritation occurs, get medical advice/attention.

P337+313 - If eye irritation persists, get medical advice/attention.

GHS Storage and Disposal P403+235 - Store in cool/well-ventilated place. P405 - Store locked up. P501 -

Phrases: Dispose of contents/container according to national and local regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Inhalation:Causes respiratory tract irritation. Harmful if inhaled.Skin Contact:Causes skin irritation. May cause allergic skin reaction.

Eye Contact:Causes eye irritation.Ingestion:Harmful if swallowed.Additional InformationNo data available.

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
1344-28-1	Aluminum oxide	50.0 -60.0 %
NA	Liquid polysulfide polymer	<30.0 %
471-34-1	Calcium carbonate	<15.0 %
78-93-3	Methyl ethyl ketone	<10.0 %
108-88-3	Toluene	< 5.0 %
1313-13-9	Manganese(IV) oxide	< 5.0 %
61788-32-7	Hydrogenated terphenyls	< 5.0 %
13463-67-7	Titanium dioxide	< 5.0 %
1333-86-4	Carbon black	< 1.0 %
102-06-7	N,N'-Diphenyl Guanidine, Coated	< 0.5 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get immediate medical attention.

In Case of Skin Contact: Remove contaminated clothing and shoes. Wash clothing before reuse. Wash

with soap and water. Get medical attention if irritation develops or persists.

In Case of Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally

lifting the upper and lower eyelids. Get medical attention/advice.

In Case of Ingestion: Do NOT induce vomiting. Never give anything by mouth to an unconscious

person. Get medical aid immediately.

Note to Physician: Treat symptomatically and supportively.

Licensed to Appli-Tec GHS format



Page: 3 of 6

Revision: 10/06/2021 Supersedes Revision: 06/13/2017

5. Fire Fighting Measures

Flash Pt: ~ 30.00 C

LEL: No data. **Explosive Limits:** UEL: No data.

No data. **Autoignition Pt:**

Suitable Extinguishing

Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Media:

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand.

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and No data available.

Hazards:

Hazardous Combustion

No data available.

Store at <= -40deq.C.

Products:

6. Accidental Release Measures

Material Is Released Or

Spilled:

Steps To Be Taken In Case Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so. Discharge into the environment must be avoided. Use proper personal protective equipment as indicated in Section 8. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

7. Handling and Storage

Precautions To Be Taken

in Handling:

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Keep away

from sources of ignition - No smoking. Wash thoroughly after handling.

Precautions To Be Taken

in Storing:

8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
1344-28-1	Aluminum oxide	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 10 mg/m3 (E)	No data.
NA	Liquid polysulfide polymer	No data.	No data.	No data.
471-34-1	Calcium carbonate	No data.	TLV: 10 mg/m3 (E)	No data.
78-93-3	Methyl ethyl ketone	PEL: 200 ppm	TLV: 200 ppm STEL: 300 ppm	No data.
108-88-3	Toluene	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 20 ppm	No data.
1313-13-9	Manganese(IV) oxide	CEIL: 5 mg/m3	TWA: 0.02 mg/m3 (resp.) 0.1 mg/m3 (IHL)	No data.
61788-32-7	Hydrogenated terphenyls	No data.	No data.	No data.
13463-67-7	Titanium dioxide	PEL: 15 (dust) mg/m3	TLV: 10 mg/m3	No data.
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3 mg/m3 (IHL)	No data.
102-06-7	N,N'-Diphenyl Guanidine, Coated	No data.	No data.	No data.

Licensed to Appli-Tec **GHS** format

Page: 4 of 6

Revision: 10/06/2021 Supersedes Revision: 06/13/2017

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure. Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or

other engineering controls to control airborne levels below recommended

exposure limits.

Work/Hygienic/Maintenanc Handle in accordance with good industrial hygiene and safety practice. Wash

hands before breaks and at the end of workday. e Practices:

9. Physical and Chemical Properties

[X] Liquid [] Solid **Physical States:**

Appearance: Gray. Paste. Appearance and Odor:

Odor: sulfide odor.

pH: No data **Melting Point:** No data. **Boiling Point:** No data. Flash Pt: ~ 30.00 C **Evaporation Rate:** No data.

Flammability (solid, gas): No data available.

Explosive Limits: LEL: No data. UEL: No data.

Vapor Pressure (vs. Air or No data.

mm Hg):

Vapor Density (vs. Air = 1): No data. Specific Gravity (Water = ~2.3

1):

Solubility in Water: No data. **Octanol/Water Partition** No data.

Coefficient:

N.D. **Percent Volatile:** No data. **Autoignition Pt:** No data. **Decomposition**

Temperature:

Viscosity: No data.

10. Stability and Reactivity

Stable [] Stability: Unstable [X]

Conditions To Avoid -Product will cure at ambient temperatures. Keep in cold storage until ready to

Instability: use.

Incompatibility - Materials No data available.

To Avoid:

Hazardous Decomposition Carbon oxides, sulfur oxides. Nitrogen oxides.

or Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -No data available.

Hazardous Reactions:

Licensed to Appli-Tec **GHS** format



Page: 5 of 6

Revision: 10/06/2021 Supersedes Revision: 06/13/2017

11. Toxicological Information

Toxicological Information: No data available. **Irritation or Corrosion:** Skin and eye irritant.

Chronic Toxicological

Suspected of damaging fertility or the unborn child.

Effects:

Carcinogenicity/Other Information:

Contains material which may cause cancer, based on animal data. Risk

depends on level and duration of exposure.

12. Ecological Information

No data available.

13. Disposal Considerations

Observe all federal, state, and local environmental regulations. **Waste Disposal Method:**

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping

Adhesives.

Name:

DOT Hazard Class:

UN1133 **UN/NA Number:**

FLAMMABLE LIQUID **Packing Group:**

Ш



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Adhesives.

UN Number: Packing Group: Ш

3 - FLAMMABLE LIQUID **Hazard Class:**

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Adhesives.

UN Number: 1133 **Packing Group:** Ш

Hazard Class: 3 - FLAMMABLE LIQUID

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1344-28-1	Aluminum oxide	No	No	Yes
NA	Liquid polysulfide polymer	No	No	No
471-34-1	Calcium carbonate	No	No	No
78-93-3	Methyl ethyl ketone	No	Yes NA	No
108-88-3	Toluene	No	Yes NA	Yes
1313-13-9	Manganese(IV) oxide	No	No	Yes-Cat. N450
61788-32-7	Hydrogenated terphenyls	No	No	No
13463-67-7	Titanium dioxide	No	No	No
1333-86-4	Carbon black	No	No	No
102-06-7	N,N'-Diphenyl Guanidine, Coated	No	No	No


Licensed to Appli-Tec **GHS** format



Page: 6 of 6

Revision: 10/06/2021 Supersedes Revision: 06/13/2017

California Proposition 65



This product can expose you to chemicals including Titanium dioxide and Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CAS#	Hazardous Components (Chemical Name)	Other US EPA or State Lists
1344-28-1	Aluminum oxide	TSCA: Inventory
NA	Liquid polysulfide polymer	TSCA: Inventory
471-34-1	Calcium carbonate	TSCA: Inventory
78-93-3	Methyl ethyl ketone	TSCA: Inventory
108-88-3	Toluene	TSCA: Inventory, 8A CAIR
		CA PROP.65: Yes: RDTox(F)
1313-13-9	Manganese(IV) oxide	TSCA: Inventory
61788-32-7	Hydrogenated terphenyls	TSCA: Inventory
13463-67-7	Titanium dioxide	TSCA: Inventory
		CA PROP.65: Yes: Canc.
1333-86-4	Carbon black	TSCA: Inventory
		CA PROP.65: Yes: Canc.
102-06-7	N,N'-Diphenyl Guanidine, Coated	TSCA: Inventory

16. Other Information

Revision Date: 10/06/2021 **Previous revision:** 06/13/2017

Additional Information About This Product:

No data available.

Company Policy or Disclaimer:

The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

Licensed to Appli-Tec GHS format