

1. Product and Company Identification

Product Code: 0176
Product Name: 0176
Company Name: Appli-Tec, Inc
 7 Industrial Way Unit 1
 Salem, NH 03079
Phone Number: (603)685-0500
Web site address: www.appli-tec.com
Emergency Contact: Contact medical emergency services
Information: Call Chemtrec for Transport Info. (800)424-9300
Intended Use: Adhesive

2. Hazards Identification

Skin Corrosion/Irritation, Category 2
Serious Eye Damage/Eye Irritation, Category 2A
Skin Sensitization, Category 1A
Toxic To Reproduction, Category 1B
Specific Target Organ Toxicity (single exposure), Category 3



GHS Signal Word: **Danger**

GHS Hazard Phrases: H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H336 - May cause drowsiness or dizziness.
 H360 - May damage fertility or the unborn child .

GHS Precautionary Phrases: P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P261 - Avoid breathing vapors,mist or spray.
 P264 - Wash hands thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves/eye protection/face protection.
 P281 - Use personal protective equipment as required.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.
 P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+313 - IF exposed or concerned: Get medical attention/advice.
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
 P337+313 - If eye irritation persists, get medical advice/attention.
 P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases: P405 - Store locked up.
 P501 - Dispose of contents/container according to national and local regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.
Inhalation: Irritating to the nose, throat and respiratory tract.
Skin Contact: Causes skin irritation. Allergic reactions are possible.
Eye Contact: Causes eye irritation.
Ingestion: Causes gastrointestinal tract irritation.
Additional Information 36% of mixture has unknown acute oral and dermal toxicity.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
1332-58-7	Kaolin	25.0 -50.0 %
68911-25-1	Fatty acids, C18-unsatd., dimers, polymers with 3,3'-[oxybis(2,1-ethanediyloxy)]bis[1-propanamine]	20.0 -45.0 %
25068-38-6	Bisphenol-a based epoxy resin	25.0 -35.0 %
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	1.0 -9.0 %
108-88-3	Toluene	0.1 -1.0 %
13463-67-7	Titanium dioxide	0.1 -1.0 %

Additional Information Exact percentages have been withheld as a trade secret.

4. First Aid Measures

Emergency and First Aid Procedures:

In Case of Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

In Case of Skin Contact: Remove contaminated clothing and shoes. Wash clothing before reuse. Wash with soap and water. Get medical attention if irritation develops or persists.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately.

In Case of Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point: > 93.00 C

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: No data.

Suitable Extinguishing Media: Water spray, Dry chemical, Carbon dioxide, Foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Use water spray to keep fire-exposed containers cool.

Flammable Properties and Hazards: No data available.

Hazardous Combustion Products: No data available.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled: Evacuate unnecessary personnel. Ventilate the area. Use proper personal protective equipment as indicated in Section 8. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. Handling and Storage

Precautions To Be Taken in Handling: Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation.

Precautions To Be Taken in Storing: Store at <= -40deg. C.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
1332-58-7	Kaolin	PEL: 15 (dust); 5 (resp.) mg/m3	TLV: 2 mg/m3 (E,R)	No data.
68911-25-1	Fatty acids, C18-unsatd., dimers, polymers with 3,3'-[oxybis(2,1-ethanedioxy)]bis[1-propanamine]	No data.	No data.	No data.
25068-38-6	Bisphenol-a based epoxy resin	No data.	No data.	No data.
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No data.	No data.	No data.
108-88-3	Toluene	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 20 ppm	No data.
13463-67-7	Titanium dioxide	PEL: 15 (dust) mg/m3	TWA: 10 mg/m3 (Total dust)	No data.

Respiratory Equipment (Specify Type): Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.): Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

Work/Hygienic/Maintenance Practices: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Appearance: Gray. Paste.
Odor: weak odor.

pH: No data.

Melting Point: No data.

Boiling Point: No data.

Flash Point: > 93.00 C

Evaporation Rate:	No data.
Flammability (solid, gas):	No data available.
Explosive Limits:	LEL: No data. UEL: No data.
Vapor Pressure:	No data.
Vapor Density (vs. Air=1):	No data.
Specific Gravity (Water=1):	~1.2
Solubility in Water:	No data.
Saturated Vapor Concentration:	No data.
Octanol/Water Partition Coefficient:	No data.
Autoignition Pt:	No data.
Decomposition Temperature:	No data.
Viscosity:	No data.

10. Stability and Reactivity

Stability:	Unstable [X] Stable []
Conditions To Avoid - Instability:	Product will cure at ambient temperatures. Keep in cold storage until ready to use.
Incompatibility - Materials To Avoid:	Strong oxidizing agents.
Hazardous Decomposition or Byproducts:	irritating and toxic fumes and gases, Nitrogen oxides, Carbon oxides.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

11. Toxicological Information

Toxicological Information: No data available.
Sensitization: Skin sensitization.
Chronic Toxicological Effects: Reproductive toxicity.
Carcinogenicity/Other Information: Ingredient CAS# 13463-67-7: IARC: Group 2B carcinogen.

12. Ecological Information

No data available.


13. Disposal Considerations

Waste Disposal Method: Observe all federal, state, and local environmental regulations.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated.
DOT Hazard Class:
UN/NA Number:



MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Environmentally Hazardous Substance, Liquid, n.o.s. (Epoxy resin)
UN Number: UN3082 **Packing Group:** III
Hazard Class: 9 - CLASS 9
IMDG MFAG Number:
Marine Pollutant: Yes

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Environmentally Hazardous Substance, Liquid, n.o.s. (Epoxy resin)
UN Number: UN3082 **Packing Group:** III
Hazard Class: 9 - CLASS 9

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1332-58-7	Kaolin	No	No	No
68911-25-1	Fatty acids, C18-unsatd., dimers, polymers with 3,3'-[oxybis(2,1-ethanedioxy)]bis[1-propanamine]	No	No	No
25068-38-6	Bisphenol-a based epoxy resin	No	No	No
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No
108-88-3	Toluene	No	Yes NA	Yes
13463-67-7	Titanium dioxide	No	No	No

California Proposition 65



WARNING

This product can expose you to chemicals including Titanium dioxide and Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
1332-58-7	Kaolin	TSCA: Inventory
68911-25-1	Fatty acids, C18-unsatd., dimers, polymers with 3,3'-[oxybis(2,1-ethanedioxy)]bis[1-propanamine]	TSCA: Inventory
25068-38-6	Bisphenol-a based epoxy resin	TSCA: Inventory
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	TSCA: Inventory
108-88-3	Toluene	TSCA: Inventory, 8A CAIR, 8C CA PROP.65: Yes: RDTox(F)
13463-67-7	Titanium dioxide	TSCA: Inventory CA PROP.65: Yes: Canc.

CAS #	Hazardous Components (Chemical Name)	International Regulatory Lists
1332-58-7	Kaolin	REACH: (P)
68911-25-1	Fatty acids, C18-unsatd., dimers, polymers with 3,3'-[oxybis(2,1-ethanedioxy)]bis[1-propanamine]	REACH: (P)
25068-38-6	Bisphenol-a based epoxy resin	REACH: (P)
4246-51-9	3,3'-Oxybis(ethyleneoxy)bis(propylamine)	REACH: (P), 01-2119963377-26: Full
108-88-3	Toluene	REACH: (P), 01-2119471310-51: Full, Res. - 48., XVII - 48
13463-67-7	Titanium dioxide	REACH: (P), 01-2119489379-17: Full

16. Other Information

Revision Date: 04/09/2024 **Previous revision:** 02/08/2024

Additional Information About This Product: No data available.

Company Policy or Disclaimer: The information on this data sheet represents our current and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or the applicable technical bulletin, or which involves using the product in combination with any other product or any other process is the responsibility of the user.